- › Air Studios Audio Tuning
- › 60 Watts per channel (FTC)

DESIGN & BUILD

- › Twin Mono Symmetrical Amplifier Design
- › Dual Isolated Power Supplies for Precision Channel Separation and Imaging
- › LAPT Output Transistors Ensure High-Speed Output Over a Broad Frequency Range with Minimal Distortion
- › Parallel Drive Schottky Barrier Diodes Provide a High Speed Attack
- › Curved Profile Glossy Aluminum Front Panel
- › Stream Direct Mode
- › Bass & Treble Control
- › Rigid Chassis Construction
- › Large Insulator Feet
- › Gold Plated Speaker terminals
- › High Quality Aluminum Remote

CONNECTIONS

- › CD
- › Phono (MM)
- › Tape In / Out
- › Aux
- › XM Ready*
- › Headphone Output

INTEGRATED TECHNOLOGIES

AIR STUDIOS
MONITOR

((XM))
R E A D Y

CONNECTIONS

Rear Panel

SPECIFICATIONS

› Weight: 10 kg / 22 lbs

› Dimensions (W x H x D) : 420 x 100 x 359 mm

UPC

› 12562960104

*XM Connect-and-Play antenna and subscription service (each sold separately) required to receive XM and XM-HD Surround Radio.
Specifications and design subject to change.
PIONEER, ELITE, and the Pioneer and Elite logos are registered trademarks of Pioneer Corporation.
XM and XM Ready are registered trademarks of XM Satellite Radio Inc.
The AIR STUDIOS logo is a trademark of Air Sudios, Inc.